## NSN 5930-00-327-7812

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-327-7812

**Thread Class:** 

2a single mounting facility

Width Between Flats:

0.190 inches single actuator

**Hazardous Locations/environmental Protection:** 

Dustproof

First Flat Length:

0.420 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.700 inches single actuator

**Individual Section Quantity:** 

1

**Longest Horizontal Distance Between Mounting Centers:** 

0.750 inches single mounting facility

**End Application:** 

B-52 stratofortress aircraft.

**Switch Contact Basic Design:** 

Pile-up

**Throw Quantity:** 

2 single section in-line

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Pile-up Contact Form Arrangement:** 

1c single switch single section in-line

**Thread Size:** 

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Mounting Facility Pattern:** 

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, parallel flatted single actuator

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Tab w/screw

## NSN 5930-00-327-7812

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

90.0 degrees single actuator

## **Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Special Features:** 

Weapon system essential

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0