# NSN 5930-00-327-7812

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-327-7812

# Thread Class:

2a single mounting facility

# Width Between Flats:

0.190 inches single actuator

# Hazardous Locations/environmental Protection:

Dustproof

#### First Flat Length:

0.420 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.700 inches single actuator

# Individual Section Quantity:

1

# Longest Horizontal Distance Between Mounting Centers:

0.750 inches single mounting facility

#### **End Application:**

B-52 stratofortress aircraft.

# Switch Contact Basic Design:

Pile-up

## **Throw Quantity:**

2 single section in-line

#### **Mounting Method:**

Threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

# Pile-up Contact Form Arrangement:

1c single switch single section in-line

#### **Thread Size:**

0.138 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

125.0 ac at sea level

#### **Mounting Facility Pattern:**

Two position in-line single mounting facility

# Switch Actuator Indexing Position Quantity:

2 single actuator

## Shaft Type:

Round, parallel flatted single actuator

# Criticality Code Justification:

Feat

#### **Terminal Type:**

Tab w/screw

NSN 5930-00-327-7812

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

## **Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Special Features:** 

Weapon system essential

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0