

View Online at <https://aerobasegroup.com/nsn/5930-00-327-8252>

**Thread Class:**

3a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.125 inches

**First Flat Length:**

0.531 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Overall Diameter:**

3.312 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

7 single section rear

**Mounting Facility Circle Radius:**

1.000 inches single mounting facility

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 ac at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Three position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0