NSN 5930-00-327-8575

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-327-8575

Th	rea	d	lه	n	nth	•
	ıca	u	ᆫ	ı١٧	441	

0.375 inches single mounting facility

First Flat Length:

0.281 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

150.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

20.0 amperes inductive load highest ac voltage rating at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-00-327-8575

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0