

View Online at <https://aerobasegroup.com/nsn/5930-00-328-0821>

**Inside Diameter:**

0.188 inches all connections

**Overall Length:**

1.880 inches

**Outside Diameter:**

0.195 inches all connections and 0.205 inches all connections

**Overall Height:**

1.310 inches

**Overall Width:**

0.380 inches

**Body Height:**

1.000 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Longest Horizontal Distance Between Mounting Centers:**

0.718 inches

**Longest Vertical Distance Between Mounting Centers:**

0.718 inches

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 71.0 degrees celsius

**Mounting Method:**

Flush and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4.00 pounds per square inch gage

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

10.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

1.55 actuation point inches of water and 1.40 deactuation point inches of water and 0.15 differential point inches of water

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Barbed, unthreaded external all connections

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0