

View Online at <https://aerobasegroup.com/nsn/5930-00-328-0821>

Inside Diameter:

0.188 inches all connections

Overall Length:

1.880 inches

Outside Diameter:

0.195 inches all connections and 0.205 inches all connections

Overall Height:

1.310 inches

Overall Width:

0.380 inches

Body Height:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Longest Horizontal Distance Between Mounting Centers:

0.718 inches

Longest Vertical Distance Between Mounting Centers:

0.718 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -55.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Flush and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

4.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

10.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1.55 actuation point inches of water and 1.40 deactuation point inches of water and 0.15 differential point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Media For Which Designed:

Gas

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0