NSN 5930-00-328-4707

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-328-4707

| New Online at https://aerobasegroup.com/nsi//3930-00-326-4707 |
|---|
| Hazardous Locations/environmental Protection: |
| Driptight |
| Overall Length: |
| 1.250 inches |
| Overall Height: |
| 0.390 inches |
| Body Diameter: |
| 0.625 inches |
| Body Height: |
| 0.390 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.109 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 0.937 inches |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Operating Tempurature Rating: |
| 350.0 degrees fahrenheit |
| Mounting Method: |
| Bracket and unthreaded hole |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 10.0 amperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point not adjustable and deactuation point not adjustable |
| Contact Stimulus Rating: |
| 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 240.0 ac at sea level first voltage |
| Frequency In Hertz: |
| 60.0 single voltage |
| Media For Which Designed: |
| Gas |
| Style Designator: |
| Disc w/flange |
| |

NSN 5930-00-328-4707

Thermostatic Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

