NSN 5930-00-328-4707

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-328-4707

Hazardous Locations/environmental Protection:
Driptight
Overall Length:
1.250 inches
Overall Height:
0.390 inches
Body Diameter:
0.625 inches
Body Height:
0.390 inches
Unthreaded Mounting Hole Diameter:
0.109 inches
Longest Horizontal Distance Between Mounting Centers:
0.937 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
350.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Excility Pottern
Mounting Facility Pattern:
Two position in-line
Two position in-line
Two position in-line Nonpile-up Contact Arrangement:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Frequency In Hertz:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Frequency In Hertz: 60.0 single voltage
Two position in-line Nonpile-up Contact Arrangement: 1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 10.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 275.00 actuation point degrees fahrenheit and 235.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 240.0 ac at sea level first voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed:

NSN 5930-00-328-4707

Thermostatic Switch - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0