

View Online at <https://aerobasegroup.com/nsn/5930-00-328-6243>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.791 inches

Body Width:

0.250 inches

Body Height:

0.356 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Switch Actuator Quantity:

1

Actuator Length:

0.580 inches

Actuator Style:

Leaf

Actuator Width:

0.160 inches

Actuator Free Position Height:

0.437 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

3.5 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.020 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Efurnished w/1 wire lead no. 24 awg, type e mil-w1687d/4 color brown, 5.600 in. Lg, attached to normally closed terminal, elongated mtg hole on actuator and common terminal end in line parallel to length

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

19565-200812 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0