

View Online at <https://aerobasegroup.com/nsn/5930-00-328-9330>

Body Style:

Bushing mounted

Overall Length:

2.450 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Diameter:

Between 0.970 inches and 1.030 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Body Length:

1.075 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

Between 1.345 inches and 1.405 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0