

View Online at <https://aerobasegroup.com/nsn/5930-00-329-6449>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

0.800 inches

**Body Width:**

0.426 inches

**Body Height:**

0.260 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches

**Actuator Length:**

0.200 inches

**Actuator Height:**

0.187 inches

**Actuator Position-action Relationship:**

Center position maintained and left position maintained and right position maintained

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 125.0 dc

**End Application:**

Sh-60b lamps mark iii helicopter, orion p-3, f-14 tomcat aircraft. General purpose electronic test equipment (gpete), all-weather anti-ship harpoon (amg-84) missile. Forrestal class cv, whidbey island class lsd, spruance class dd (963), yellowstone class ad-41, nimitz class cvn.

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

4 pole, single throw, dual contact, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

0.500 amperes resistive dc and 3.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0