

View Online at <https://aerobasegroup.com/nsn/5930-00-329-6449>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

0.800 inches

Body Width:

0.426 inches

Body Height:

0.260 inches

Unthreaded Mounting Hole Diameter:

0.100 inches

Actuator Length:

0.200 inches

Actuator Height:

0.187 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

End Application:

Sh-60b lamps mark iii helicopter, orion p-3, f-14 tomcat aircraft. General purpose electronic test equipment (gpete), all-weather anti-ship harpoon (amg-84) missile. Forrestal class cv, whidbey island class lsd, spruance class dd (963), yellowstone class ad-41, nimitz class cvn.

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

4 pole, single throw, dual contact, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 3.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0