NSN 5930-00-329-6963

Pressure Switch - Page 1 of 2

28.0 dc at sea level single voltage



View Online at https://aerobasegroup.com/nsn/5930-00-329-6963

Thread Class: 3a single pressure connection **Thread Length:** 0.275 inches single pressure connection **Overall Length:** 3.700 inches **Outside Diameter:** 0.438 inches single connection **Body Length:** 2.062 inches **Overall Diameter:** 1.070 inches **Pressure Switch Type:** Gage **Operating Tempurature Rating:** Between -40.0 degrees celsius and 60.0 degrees celsius **Mounting Method:** Inlet connection **Features Provided:** Electrical box connector Thready Qty Per Inch (tpi): 20 single pressure connection **Contact Action Stimulus:** Decrease **Proof Pressure:** 37.50 pounds per square inch **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Sensing Element Burst Pressure:** 75.00 pounds per square inch **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 1.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 12.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage **Contact Voltage Rating In Volts:**

NSN 5930-00-329-6963

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unc single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0