

View Online at <https://aerobasegroup.com/nsn/5930-00-329-8094>

Thread Class:

2a single mounting facility

Thread Length:

0.313 inches single mounting facility

Width Between Flats:

0.186 inches single actuator and 0.188 inches single actuator

Overall Length:

1.500 inches

Overall Height:

Between 1.546 inches and 1.578 inches

Overall Width:

Between 1.234 inches and 1.266 inches

First Flat Length:

0.234 inches single actuator and 0.266 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.672 inches single actuator and 0.704 inches single actuator

Nonturn Device Radius:

0.515 inches at 3: 00 o'clock and 0.547 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-40.0/+65.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

3 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

6.0 lowest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+15.000/+25.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level and 3.5 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0