## NSN 5930-00-329-8217

Rotary Switch - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5950-00-529-6217      |
|--|
| Individual Section Quantity:                                       |
| 1  |
| Longest Horizontal Distance Between Mounting Centers:              |
| 1.000 inches single mounting facility                              |
| Mounting Method:   |
| Base single mounting facility                                      |
| Thready Qty Per Inch (tpi):  |
| 32 single mounting facility  |
| Thread Size:   |
| 0.138 inches single mounting facility                              |
| Contact Voltage Rating In Volts:                                   |
| 500.0 lowest dc voltage rating at sea level                        |
| Mounting Facility Pattern:   |
| Two position in-line single mounting facility                      |
| Switch Actuator Indexing Position Quantity:                        |
| 12 single actuator   |
| Shaft Type:  |
| Round single actuator  |
| Terminal Type:   |
| Tab, solder lug  |
| Switch Actuator Positioning Increment:                             |
| 30.0 degrees single actuator                                       |
| Contact Load Current Rating:                                       |
| 10.0 amperes resistive load highest ac voltage rating at sea level |
| Thread Series Designator:  |
| Unc single mounting facility                                       |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

Fiig: A052b0