

View Online at <https://aerobasegroup.com/nsn/5930-00-331-1320>

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.125 inches

Overall Height:

1.938 inches

Overall Width:

1.516 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.625 inches single actuator

Nonturn Device Radius:

0.531 inches at 10: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 10: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

7 dummy terminals on front of section one 7 dummy terminals on rear of section two

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0