## NSN 5930-00-331-2203

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-331-2203 **Thread Class:** 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 3.063 inches **Overall Height:** 1.875 inches **Overall Width:** 1.593 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.688 inches single actuator **Nonturn Device Radius:** 0.531 inches at 12: 00 o'clock **Individual Section Quantity:** 4 **Nonturn Device Type:** Tab at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 5 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks 4th section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## **NSN 5930-00-331-2203**Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
0.5 amperes resistive load ac at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0