NSN 5930-00-331-3704

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-331-3704

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.594 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Individual Section Quantity:

1

Operating Tempurature Range:

-25.0/+65.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section periphery

Throw Quantity:

2 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.344 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load lowest ac voltage rating at sea level

NSN 5930-00-331-3704Rotary Switch - Page 2 of 2



| Precious Material And Location: |
|--|
| Terminals silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Snap or line |
| Thread Series Designator: |
| Uns single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A052b0