# NSN 5930-00-332-0041

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-332-0041

# **Thread Class:**

2b single mounting facility

# **Overall Length:**

Between 2.221 inches and 2.283 inches

# **Overall Height:**

3.500 inches

## **Overall Width:**

3.500 inches

#### First Flat Length:

0.500 inches single actuator

#### Flat Height:

0.218 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.940 inches single actuator

# Individual Section Quantity:

1

# Longest Horizontal Distance Between Mounting Centers:

3.000 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

3.000 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 single section rear

#### **Throw Quantity:**

36 single section rear

#### **Mounting Method:**

Threaded hole single mounting facility

#### **Thread Size:**

0.138 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

125.0 ac at sea level

#### Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

## Mounting Facility Pattern:

Four position rectangular single mounting facility

# Switch Actuator Indexing Position Quantity:

36 single actuator

Shaft Type:

Round, flatted single actuator

# NSN 5930-00-332-0041

Rotary Switch - Page 2 of 2



**Terminal Type:** 

Turret

**Contact Switching Action:** 

Breaks before makes single section rear

Switch Actuator Positioning Increment:

10.0 degrees single actuator

# **Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

# Style Designator:

Tap, square frame

#### **Thread Series Designator:**

Unf single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A052b0