

View Online at <https://aerobasegroup.com/nsn/5930-00-332-0778>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.168 inches and 0.208 inches

**Body Length:**

0.626 inches

**Body Width:**

0.326 inches

**Body Height:**

Between 0.580 inches and 0.620 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.091 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.055 inches and 0.065 inches

**Actuator Height:**

0.135 inches

**Actuator Free Position Height:**

0.410 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

17.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes inductive dc and 4.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac and 1.000 amperes lamp ac and 4.000 amperes motor ac

**Test Data Document:**

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0