

View Online at <https://aerobasegroup.com/nsn/5930-00-332-0783>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

1.270 inches

**Body Width:**

0.625 inches

**Body Height:**

0.910 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.630 inches and 0.720 inches

**Actuator Width:**

Between 0.855 inches and 0.895 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0