NSN 5930-00-333-0066

Rotary Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-00-333-0066

Thread Class:

2a single mounting facility

Thread Length:

0.430 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.010 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.205 inches single actuator and 0.215 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.760 inches single actuator

Overall Diameter:

1.500 inches

Individual Section Quantity:

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

7 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, flatted single actuator

NSN 5930-00-333-0066Rotary Switch - Page 2 of 2

A052b0



Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks 4th section rear
Switch Actuator Positioning Increment:
22.5 degrees single actuator
Detent Rotational Torque Range:
+2.000/+8.000 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: