NSN 5930-00-333-0067

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Style Designator:Tap, circuit selector



View Online at https://aerobasegroup.com/nsn/5930-00-333-0067

Explosion proof
Overall Length:
3.313 inches
Overall Height:
2.875 inches
Overall Width:
2.375 inches
Unthreaded Mounting Hole Diameter:
0.156 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
1.641 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.641 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
3 each section front
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
10.0 amperes resistive load ac at sea level

NSN 5930-00-333-0067

Rotary Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0