

View Online at <https://aerobasegroup.com/nsn/5930-00-333-6012>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Actuator Style:

Round

Actuator Free Position Height:

Between 1.688 inches and 1.750 inches

Housing Height:

1.781 inches

Housing Length:

2.437 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

28.0 ounces

Switch Actuating Force:

62.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.219 overtravel inches and 0.296 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0