

View Online at <https://aerobasegroup.com/nsn/5930-00-333-6012>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Actuator Style:**

Round

**Actuator Free Position Height:**

Between 1.688 inches and 1.750 inches

**Housing Height:**

1.781 inches

**Housing Length:**

2.437 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.000 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

28.0 ounces

**Switch Actuating Force:**

62.0 ounces

**Actuator Movement:**

Between 0.078 pretravel inches and 0.219 overtravel inches and 0.296 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.500 amperes resistive dc

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0