# NSN 5930-00-333-6127

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-333-6127

## **Thread Class:**

2a single mounting facility

### Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

5.750 inches

#### **Overall Height:**

2.312 inches

### **Overall Width:**

2.172 inches

#### First Flat Length:

0.250 inches single actuator

### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.688 inches single actuator

## Individual Section Quantity:

7

Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

### Throw Quantity:

17 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### Thread Size:

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

18 single actuator

### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

### Switch Actuator Positioning Increment:

20.0 degrees single actuator

# NSN 5930-00-333-6127

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

0.5 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0