NSN 5930-00-333-8905

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-333-8905

View Online at https://aerobasegroup.com/nsn/5930-00-333-8905
Body Style:
Hole mount
Hazardous Locations/environmental Protection:
Dustproof and explosion proof
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.080 inches
Body Length:
3.760 inches
Body Width:
0.679 inches
Body Height:
0.679 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.400 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Ad1 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
32
Nonpile-up Contact Arrangement:
4 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 1.000 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

Special Features:

inductive ac and 1.000 amperes lamp ac

Mtg holes diagonally spaced on 0.688 in. By 1.080 in. Mtg centers

NSN 5930-00-333-8905

Push Switch - Page 2 of 2



Thread	Series	Designator:
--------	--------	--------------------

Unc

Terminal Type And Quantity:

20 tab, solder lug and 1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0