NSN 5930-00-334-8921

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-334-8921

First Flat Length:

0.562 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.875 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.219 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.219 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

4 single section front

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Threaded stud

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

NSN 5930-00-334-8921

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0