NSN 5930-00-334-8933

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-334-8933

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
6.125 inches
Overall Height:
6.374 inches
Overall Width:
3.812 inches
First Flat Length:
1.000 inches single actuator
Flat Height:
0.250 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.310 inches single mounting facility and 0.317 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
04009
Knob Specificationial Markings:
Arrow
Longest Horizontal Distance Between Mounting Centers:
5.812 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Pole Quantity:
1 3rd section rear
Throw Quantity:
2 1st section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
250.0 ac at sea level
Switch Actuator Momentary Position:
Counterclockwise single actuator
Rotor Through Connection Quantity:

1 each section

NSN 5930-00-334-8933

Rotary Switch - Page 2 of 2



Mounting Facility Pattern: Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes 2nd section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Contact Load Current Rating:** 25.0 amperes resistive load ac at sea level **Style Designator:** Tap, circuit selector Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A052b0