

View Online at <https://aerobasegroup.com/nsn/5930-00-334-8950>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

13.438 inches

First Flat Length:

1.250 inches single actuator

Flat Height:

0.250 inches single actuator

Shaft Diameter:

0.625 inches single actuator

Shaft Length:

1.562 inches single actuator

Unthreaded Mounting Hole Diameter:

0.531 inches 2nd mounting facility and 0.625 inches 2nd mounting facility

Individual Section Quantity:

6

Knob Manufacturer Code:

82121

Knob Specificationial Markings:

Arrow

Longest Horizontal Distance Between Mounting Centers:

3.250 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

8.000 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 each section front

Throw Quantity:

2 each section rear

Mounting Method:

Bracket 2nd mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

100.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0