

View Online at <https://aerobasegroup.com/nsn/5930-00-334-8951>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.312 inches

**First Flat Length:**

0.750 inches single actuator

**Flat Height:**

0.312 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.062 inches single actuator

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

04009

**Knob Specificationial Markings:**

Arrow

**Longest Horizontal Distance Between Mounting Centers:**

2.125 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.312 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section periphery

**Throw Quantity:**

1 each section periphery

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Switch Actuator Momentary Position:**

Counterclockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

25.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0