NSN 5930-00-334-8954

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-334-8954

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
5.562 inches
Overall Height:
7.500 inches
Overall Width:
5.500 inches
First Flat Length:
0.750 inches single actuator
Flat Height:
0.312 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.062 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
04009
Knob Specificationial Markings:
Arrow
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
2 each section front
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
250.0 ac at sea level
Switch Actuator Momentary Position:

Counterclockwise single actuator

NSN 5930-00-334-8954Rotary Switch - Page 2 of 2

No Fiig: A052b0



Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:
Threaded stud
Contact Switching Action:
Makes before breaks, breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: