NSN 5930-00-337-6283

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-337-6283

Thread Class:

3a single pressure connection

Thread Length:

0.239 inches single pressure connection

Overall Length:

1.549 inches

Outside Diameter:

0.375 inches single connection

Body Length:

1.000 inches

Overall Diameter:

1.230 inches

Pressure Switch Type:

Absolute

Operating Tempurature Rating:

Between -55.0 degrees fahrenheit and 204.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

24 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch absolute

Thread Size:

0.375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Turret

Contact Load Current Rating:

3.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

NSN 5930-00-337-6283

Pressure Switch - Page 2 of 2



Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0