

View Online at <https://aerobasegroup.com/nsn/5930-00-337-8050>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.500 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Length:

0.370 inches

Actuator Style:

Leaf

Actuator Width:

0.235 inches

Actuator Free Position Height:

0.390 inches

Actuator Adapter Style:

Leaf

Housing Length:

0.500 inches

Housing Width:

0.200 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

0.188 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

0.350 inches

Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Pile-up Contact Form Arrangement:

1c single position

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive dc and 7.000 amperes resistive ac

Special Features:

Current rating 2.5amp at50000 ft

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0