

View Online at <https://aerobasegroup.com/nsn/5930-00-337-8050>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

0.500 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

0.087 inches

**Actuator Length:**

0.370 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.235 inches

**Actuator Free Position Height:**

0.390 inches

**Actuator Adapter Style:**

Leaf

**Housing Length:**

0.500 inches

**Housing Width:**

0.200 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

0.188 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

0.350 inches

**Maximum Voltage Rating In Volts:**

230.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Pile-up Contact Form Arrangement:**

1c single position

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 7.000 amperes resistive dc and 7.000 amperes resistive ac

**Special Features:**

Current rating 2.5amp at50000 ft

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0