

View Online at <https://aerobasegroup.com/nsn/5930-00-340-5506>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

9.688 inches

First Flat Length:

1.594 inches single actuator

Shaft Diameter:

0.312 inches single actuator

Shaft Length:

1.969 inches single actuator

Overall Diameter:

2.812 inches

Individual Section Quantity:

16

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.250 inches single mounting facility

Operating Temperature Range:

-85.0/+185.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

5 each section periphery

Mounting Method:

Bracket single mounting facility and threaded stud single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0