## NSN 5930-00-340-6902

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-340-6902

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

First Flat Length:

0.468 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.912 inches single actuator

**Individual Section Quantity:** 

1

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

3 single section rear

**Throw Quantity:** 

2 single section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Metallic inclosure

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

15.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load dc at sea level

## NSN 5930-00-340-6902

Rotary Switch - Page 2 of 2



T	hre	ead	<b>Series</b>	Desig	ınator
-			-0	- 00.9	

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0