## NSN 5930-00-342-0502

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-342-0502

View Online at https://aerobasegroup.com/nsn/5930-00-342-0502
Hazardous Locations/environmental Protection:
Dustproof and moisture resistant and salt spray resistant and vibration resistant
Overall Height:
0.607 inches
Body Height:
0.364 inches
Overall Diameter:
0.640 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -80.0 degrees fahrenheit and 550.0 degrees fahrenheit
Mounting Method:
Surface
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load first voltage2.5 amperes resistive load second voltage1.0 amperes resistive load third voltage5.0 amperes
resistive load fourth voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
165.00 actuation point degrees fahrenheit and 330.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 ac at sea level first voltage125.0 ac at sea level second voltage250.0 ac at sea level third voltage30.0 dc at sea level fourth voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Disc
Shelf Life:

\_\_

N/a

**Unit Of Measure:** 

## NSN 5930-00-342-0502

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0