

View Online at <https://aerobasegroup.com/nsn/5930-00-344-1786>

Thread Length:

0.385 inches single pressure connection

Overall Length:

2.323 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.375 inches

Overall Diameter:

1.312 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Mounting Method:

Clamp

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

30.00 pounds per square inch absolute

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

75.00 pounds per square inch absolute

Terminal Type:

Wire hook

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

13.50 actuation point pounds per square inch absolute and 14.50 deactuation point pounds per square inch absolute and 1.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

30.0 dc at altitude single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0