

View Online at <https://aerobasegroup.com/nsn/5930-00-345-6860>

Body Style:

Bushing mounted

Body Diameter:

0.343 inches

Bushing Length:

0.282 inches

Case Material:

Metal

Actuator Diameter:

0.156 inches

Actuator Height:

0.136 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Detecting set radar, an/apr-3 (v)2; deep submergence systems programs (dssp); aircraft, c-2a (reprocured); sturgeon class ssn (637); helicopter, mh-53e; ticonderoga class cg (47); helicopter, search and rescue, hh-60h; helicopter, advance attack, ah-1w; aircraft, (ac-130h, mc-130h, ec-130e, hc-130)

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac

Special Features:

Weapon system essential

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-s-8805/96 government specification

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0