NSN 5930-00-346-7014

Pressure Switch - Page 1 of 2

Overall Length: 3.260 inches

Outside Diameter:

Pressure Connector Type:

Grooved, unthreaded external single connection



View Online at https://aerobasegroup.com/nsn/5930-00-346-7014

0.739 inches single connection
Overall Height:
0.985 inches
Overall Width:
3.040 inches
Body Length:
1.880 inches
Unthreaded Mounting Hole Diameter:
0.217 inches
Distance Between Mounting Facility Centers:
1.520 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
165.00 pounds per square inch
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Sensing Element Burst Pressure:
600.00 pounds per square inch
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
80.00 actuation point pounds per square inch and 110.00 deactuation point pounds per square inch
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage

NSN 5930-00-346-7014 Pressure Switch - Page 2 of 2



Media For Which Designed:
Liquid
Style Designator:
Cylindrical w/mounting lugs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0