

View Online at <https://aerobasegroup.com/nsn/5930-00-346-7014>

Overall Length:

3.260 inches

Outside Diameter:

0.739 inches single connection

Overall Height:

0.985 inches

Overall Width:

3.040 inches

Body Length:

1.880 inches

Unthreaded Mounting Hole Diameter:

0.217 inches

Distance Between Mounting Facility Centers:

1.520 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

165.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

600.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

80.00 actuation point pounds per square inch and 110.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Grooved, unthreaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0