

View Online at <https://aerobasegroup.com/nsn/5930-00-346-7989>

Thread Class:

3a single threaded bushing

Hazardous Locations/environmental Protection:

Vibration resistant and humidity resistant and salt spray resistant

Overall Length:

3.270 inches

Overall Height:

0.860 inches

Overall Width:

1.570 inches

Body Length:

2.223 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -10.0 degrees celsius and 60.0 degrees celsius

Mounting Method:

Threaded bushing

Features Provided:

Electrical box connector

Thready Qty Per Inch (tpi):

20 single threaded bushing

Contact Action Stimulus:

Increase

Proof Pressure:

300.00 pounds per square inch gage

Thread Size:

0.438 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

50.00 actuation point pounds per square inch and 20.00 deactuation point pounds per square inch and 30.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external all connections

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0