NSN 5930-00-347-1699

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-347-1699

Thread Class:
3b single pressure connection
Inside Diameter:
0.245 inches single connection
Thread Length:
0.625 inches single pressure connection
Overall Length:
4.125 inches
Body Diameter:
1.437 inches
Body Length:
2.230 inches
Overall Diameter:
1.440 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 225.0 degrees fahrenheit
Mounting Method:
Clamp
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.4375 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained
Sensing Element Burst Pressure:
7500.00 pounds per square inch
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
5.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:

700.00 actuation point pounds per square inch gage and 450.00 deactuation point pounds per square inch gage and 250.00 differential

point pounds per square inch gage Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

NSN 5930-00-347-1699

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0