

View Online at <https://aerobasegroup.com/nsn/5930-00-349-0049>

Hazardous Locations/environmental Protection:

Corrosion resistant and dust resistant and explosion resistant

Overall Length:

3.750 inches

Overall Height:

6.516 inches

Overall Width:

3.469 inches

Body Height:

6.250 inches

Unthreaded Mounting Hole Diameter:

0.344 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

8.500 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.875 inches

Longest Vertical Distance Between Mounting Centers:

5.500 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

160.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port and tubing end seal connection

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+25.00/+125.00 actuation point degrees fahrenheit and +25.00/+125.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

600.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0