## NSN 5930-00-349-6872

**Hazardous Locations/environmental Protection:** 

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-349-6872

Watertight
Overall Height:
4.625 inches
Overall Width:
4.375 inches
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
15605
Longest Horizontal Distance Between Mounting Centers:
4.875 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.500 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
1 each section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

Breaks before makes each section front

## NSN 5930-00-349-6872

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:** 

4.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:** 

Switch marked auto-manual

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A052b0