

View Online at <https://aerobasegroup.com/nsn/5930-00-350-7776>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

Between 0.620 inches and 0.630 inches

**Bushing Length:**

Between 0.680 inches and 0.720 inches

**Body Length:**

Between 1.790 inches and 1.830 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.020 inches

**Actuator Height:**

0.020 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.938 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

6 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0