

View Online at <https://aerobasegroup.com/nsn/5930-00-351-7121>

Thread Class:

2a single mounting facility

Thread Length:

0.307 inches single mounting facility and 0.317 inches single mounting facility

Overall Length:

Between 1.745 inches and 1.755 inches

First Flat Length:

0.370 inches single actuator and 0.380 inches single actuator

Flat Height:

0.199 inches single actuator and 0.209 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.745 inches single actuator and 0.755 inches single actuator

Overall Diameter:

Between 1.557 inches and 1.567 inches

Nonturn Device Radius:

0.526 inches at 3: 00 o'clock and 0.536 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0