

View Online at <https://aerobasegroup.com/nsn/5930-00-355-4560>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

1.000 inches

Bushing Length:

0.470 inches

Body Length:

1.638 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc

Special Features:

Solenoid hold in for the down position

Test Data Document:

81349-mils5594 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0