## NSN 5930-00-356-2396

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-356-2396

## Thread Length:

0.312 inches single mounting facility

#### Width Between Flats:

0.189 inches single actuator

**Overall Length:** 

2.359 inches

#### **Overall Height:**

1.516 inches

#### **Overall Width:**

1.516 inches

#### First Flat Length:

0.282 inches single actuator

#### **Shaft Diameter:**

0.250 inches single actuator

#### **Shaft Length:**

0.407 inches single actuator

#### **Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

## **Individual Section Quantity:**

4

## **Nonturn Device Type:**

Tab at 3: 00 o'clock

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section front

## **Throw Quantity:**

6 each section rear

# Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### **Rotor Through Connection Quantity:**

2 each section

#### **Switch Actuator Indexing Position Quantity:**

6 single actuator

#### **Shaft Type:**

Round, parallel flatted, threaded hole single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-356-2396

Rotary Switch - Page 2 of 2



Switch	<b>Actuator</b>	<b>Positioning</b>	Increment:
SWILCII	Actuator	r ositioning	micrement.

30.0 degrees single actuator

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0